


SERIE OKRĄGŁE OBCIĄŻENIE DUŻE

ROUND SERIES HEAVY LOAD

RR




	D	d	L ₀	R	XLL 20% Ugięcie dla długiej trwałości Extra long life deflection		MAX 37,5% Max ugięcie robocze Max working deflection	
Symbol Ctlg. No.	Gniazdo Housing Ømm	Trzpień Rod Ømm	Długość swobodna Free length mm	Sztywność Rate N/mm	Ugięcie Stroke mm	Obciążenie Load N	Ugięcie Stroke mm	Obciążenie Load N
RR10025	10	5	25	20,7	5,0	104	7,5	155
RR10032			32	16,1	6,4	103	9,6	155
RR10038			38	13,0	7,6	99	11,4	148
RR10045			44	10,9	8,8	96	13,2	144
RR10050			51	9,6	10,2	98	15,3	147
RR10065			64	7,7	12,8	99	19,2	148
RR10075			76	6,3	15,2	96	22,8	144
RR10303			305	1,5	61,0	92	91,5	137
RR13025	12,5	6,3	25	37,5	5,0	188	7,5	281
RR13032			32	28,9	6,4	185	9,6	277
RR13038			38	23,5	7,6	179	11,4	268
RR13045			44	19,6	8,8	172	13,2	259
RR13050			51	17,3	10,2	176	15,3	265
RR13065			64	13,5	12,8	173	19,2	259
RR13075			76	11,2	15,2	170	22,8	255
RR13090			89	9,5	17,8	169	26,7	254
RR13303			305	2,7	61,0	165	91,5	247
RR16025	16	8	25	81,6	5,0	404	7,5	612
RR16032			32	61,3	6,4	392	9,6	588
RR16038			38	49,9	7,6	379	11,4	569
RR16045			44	40,8	8,8	359	13,2	539
RR16050			51	35,6	10,2	363	15,3	545
RR16065			64	27,8	12,8	356	19,2	534
RR16075			76	22,8	15,2	347	22,8	520
RR16090			89	19,6	17,8	349	26,7	523
RR16101			102	17,0	20,4	347	30,6	520
RR16303			305	5,4	61,0	329	91,5	494

Sprężyny

SERIE OKRĄGŁE ZWIJKI NIERDZEWNE

ROUND SERIES LONG STAINLESS STEEL

RI



	De	Di	d	L ₀	P
Symbol Ctlg. No.	Średnica zewnętrzna External diameter Ømm	Średnica wewnętrzna Internal diameter Ømm	Przekrój drutu Wire section Ø mm	Długość swobodna Free length mm	Skok Pitch mm
RI03300	3	2,0	0,4	300	1,04
RI04300	4	2,6	0,6	300	1,50
RI06300	6	4,0	0,9	300	2,00
RI08300	8	5,4	1,2	300	2,80
RI10300	10	6,5	1,5	300	3,50
RI12300	12	8,0	1,8	300	4,30
RI14300	14	9,3	2,2	300	4,80
RI16300	16	10,7	2,5	300	5,50
RI18300	18	12,0	2,8	300	5,30
RI20300	20	13,5	3,0	300	6,80
RI22300	22	14,7	3,5	300	6,70
RI25300	25	16,8	4,0	300	8,20

RI

seria sprężyn nierdzewnych

Sprężyny serii RI mają długość 300 mm i średnicę od 3 do 25 mm. RI to sprężyny o stałym skoku spiralne i nie są spłaszczane na końcach; nadają się do cięcia na wymiar, według Twoich potrzeb.

Wykonane są ze stali nierdzewnej, co zapewnia większą odporność na wysokie temperatury i korozję.

RI

the Stainless Steel series

The springs of the RI series have a length of 300 mm and diameters ranging from 3 to 25 mm. The RIs are springs with a constant pitch spiral and are not flattened at the ends; lend themselves to be cut to size, according to your needs.

They are made of stainless steel for greater resistance to high temperatures and corrosion.